

Specifications

evo® **Denali PVC-FREE** pattern meets or exceeds all Type II requirements of CCC-W-408A/D and W-101.

Specifications:	Performance:
Weight (Avg.):	20 oz/ly (452 gr/m ²)
Content:	Olefin Composite
Width:	52/54" (132/137 cm)
Backing:	Osnaburg
Installation:	Reverse hang / Random match
	Repeat: V: 18" H: 13.25"

Custom colors, widths and microventing are available.

Fire Safety

Class A – ASTM E-84 (GRC)
NFPA 101 Life Safety Code
CAN ULC/S102
EN13501 (B-S1-d0)

Environmental Safety

PVC-FREE
Phthalate Free
Health Product Declaration
Free of Antimicrobials
Meets State of Washington Building Specification for Indoor Air Quality
Meets California Section 01350 Indoor Air Quality Standard
Aggressive manufacturing materials recovery and reuse program
Highly cleanable water-based inks
Free of Halogenated flame retardants
20% Recycled Content
Prop 65 Compliant

USGBC LEED Support

Supports USGBC LEED v4.1 Criteria
Materials and Resources; Building Product Disclosure and Optimization
(Includes Recycled Content; Construction Waste Management; HPD's)
Indoor Environmental Quality; Low emitting materials

Moisture, Mold and Mildew

evo® PVC-FREE wallcoverings function as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use and installation of vapor barriers.

Warranty

evo® PVC-FREE is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, Permavent, warranty and other Versa innovations, visit our website at versadesignedsurfaces.com.



VERSA®
DESIGNED SURFACES