

# Specifications

evo® **Zura PVC-FREE** pattern meets or exceeds all Type II requirements of CCC-W-408A/D and W-101.

<b>Specifications:</b>	<b>Performance:</b>
<b>Weight (Avg.):</b>	20 oz/ly (452 gr/m <sup>2</sup> )
<b>Content:</b>	Olefin Composite
<b>Width:</b>	52/54" (132/137 cm)
<b>Backing:</b>	Osnaburg
<b>Installation:</b>	Reverse hang / Random match
	Repeat: V: 18" H: 13.25"

Custom colors, widths and microventing are available.

## Fire Safety

Class A – ASTM E-84 (GRC)  
NFPA 101 Life Safety Code  
CAN ULC/S102  
EN13501 (B-S1-d0)

## Environmental Safety

PVC-FREE  
Phthalate Free  
Health Product Declaration  
Free of Antimicrobials  
Meets State of Washington Building Specification for Indoor Air Quality  
Meets California Section 01350 Indoor Air Quality Standard  
Aggressive manufacturing materials recovery and reuse program  
Highly cleanable water-based inks  
Free of Halogenated flame retardants  
20% Recycled Content  
Prop 65 Compliant

## USGBC LEED Support

Supports USGBC LEED v4.1 Criteria  
Materials and Resources; Building Product Disclosure and Optimization  
(Includes Recycled Content; Construction Waste Management; HPD's)  
Indoor Environmental Quality; Low emitting materials

## Moisture, Mold and Mildew

evo® PVC-FREE wallcoverings function as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use and installation of vapor barriers.

## Warranty

evo® PVC-FREE is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, Permavent, warranty and other Versa innovations, visit our website at [versadesignedsurfaces.com](http://versadesignedsurfaces.com).



**VERSA®**  
DESIGNED SURFACES