

# FASTRAK

— WALLCOVERING —

IN STOCK - EUROPE

## **SPECIFICATIONS**

FASTRAK patterns meet or exceed Type I requirements of CCC-W-408D and W-101.

## **PERFORMANCE SPECIFICATIONS**

Weight (Avg): 15 oz (340 gr/m<sup>2</sup>)  
Backing: Scrim  
Installation: Reverse Hang/Random Match  
Roll Size: 52-54" (132/137 cm) x 30 ly (27.4m)  
GB18585-2001 Harmful Substance Testing (Pass)  
GB/T 1741-2007 Resistance to Mold (Grade 0)  
Low VOC CA01350 (Indoor Air Quality)

## **FIRE HAZARD CLASSIFICATION**

Euroclass EN13501 (B-S1-d0)  
Meets BS476 Part 6/7-British Class 0  
Class A – ASTM E84

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and the wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated. Further protection against mold growth may be achieved by microventing. Contact your supplier for additional information.

## **WARRANTY**

FASTRAK products are guaranteed to be free of defects in workmanship and material for five years.